

# VOLKSWAGEN (VW) (EU) GOLF V 1K1

## GOLF V 1.6 16V FSI (2003-2008)

**ENGINE** BAG, BLF, BLP  
Capacity: 3,5 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SynGold LL-III Premium 0W-30</b>	<b>SynGold LL-III Premium 5W-30</b>	<b>SynGold LL-III Plus 5W-30</b>

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SynGold LL-III Premium 0W-30</b>	<b>SynGold LL-III Premium 5W-30</b>	<b>SynGold LL-III Plus 5W-30</b>

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>SynGold 5W-30</b>		

Change every 15000 km/ 12 months

**TRANSAXLE AUTOMATIC** 09G 6/1  
Capacity: 7 liter (Initial fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SynMulti ATF 5+</b>		

Check every 48 months/ 60000 km

**TRANSAXLE MANUAL** 0AG 6/1  
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SynTrag Multi MTF 75W-80</b>	<b>Hypoid GL-4/GL-5 75W</b>	

Check every 48 months/ 60000 km

# VOLKSWAGEN (VW) (EU) GOLF V 1K1

## GOLF V 1.6 16V FSI (2003-2008)

**HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Brake Fluid Super LV DOT 4</b>		

Change every 24 months

**COOLING SYSTEM**

Capacity: 5,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Antifreeze LL 13</b>		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.